





REV	ECN NO	CONTENT	DATE	ENGINEER
A0		INITIAL RELEASE	/	LYL



技术参数：

- 1.额定电流：1.0A DC/AC.
- 2.额定电压：50V DC/AC.
- 3.耐电压：500V AC/minute.
- 4.接触电阻：20mΩ Max.
- 5.绝缘电阻：100MΩ Min.
- 6.工作温度：-25 ~+85



2*2P结构样式

2*3P结构样式



2*4P结构样式

2*5P结构样式





CKT	DIM A	DIM B	DIM C	DIM D	DIM E
2*2	1.00	3.60	2.00	3.42	5.00
2*3	2.00	4.60	3.00	4.42	6.00
2*4	3.00	5.60	4.00	5.42	7.00
2*5	4.00	6.60	5.00	6.42	8.00
2*6	5.00	7.60	6.00	7.42	9.00
2*7	6.00	8.60	7.00	8.42	10.00
2*8	7.00	9.60	8.00	9.42	11.00
2*9	8.00	10.60	9.00	10.42	12.00
2*10	9.00	11.60	10.00	11.42	13.00
2*11	10.00	12.60	11.00	12.42	14.00
2*12	11.00	13.60	12.00	13.42	15.00
2*13	12.00	14.60	13.00	14.42	16.00
2*14	13.00	15.60	14.00	15.42	17.00
2*15	14.00	16.60	15.00	16.42	18.00
2*16	15.00	17.60	16.00	17.42	19.00
2*17	16.00	18.60	17.00	18.42	20.00
2*18	17.00	19.60	18.00	19.42	21.00
2*19	18.00	20.60	19.00	20.42	22.00
2*20	19.00	21.60	20.00	21.42	23.00
2*21	20.00	22.60	21.00	22.42	24.00
2*22	21.00	23.60	22.00	23.42	25.00
2*23	22.00	24.60	23.00	24.42	26.00
2*24	23.00	25.60	24.00	25.42	27.00
2*25	24.00	26.60	25.00	26.42	28.00

序号	产品名称	材料规格	表面处理/颜色	数量
1	胶芯	LCP	本色	1
2	端子	铜合金	镀金/镀镍	/
3	焊片	铜合金	镀锡/镀镍	2
4	吸取盖	LCP	黑色	1

THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE PRIOR WRITTEN PERMISSION. PDWG NO:0456—1		深圳市步步精科技有限公司					
		.X: ±0.38 .X': ±3" .XX: ±0.25 .X'': ±2" .XXX: ±0.13 .XX': ±1"		NAME: 针座 SHLD1.0-2x6P B型 双排 立贴 带扣 4代 无柱 米黄色 加盖编带			
	APPD	JM_Zheng			PJ NO: 123-244-120003-X3G		
	CHKD	LYX			SIZE:A4	DRW NO:	
		DR	LYL		FINISH:SEE NOTES		MAT'L:SEE NOTES
				SCALE:N/A	REV:A0	UNIT:mm	PAGE: 1/3

NOTE(注):

1. 10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE $\pm 0.2\text{mm}$.
(10片孔距累积公差 $\pm 0.2\text{mm}$.)
2. CARRIER CAMBER NOT TO EXCEED 1mm IN 100mm.
(载带拱/弧形MAX: 1/100mm.)
3. ALL DIMENSIONS MEET EIA-481 REQUIREMENTS.
(所有的尺寸要满足协会EIA-481规范.)
4. MATERIAL: CLEAR ANTISTATIC PS, COLD SEALING.
(载带材料: 透明抗静电 PS.)
5. THICKNESS: $0.35 \pm 0.05\text{mm}$. (载带厚度: $0.35 \pm 0.05\text{mm}$.)
6. PACKING LENGHT PER REEL: 12.48 METERS. (每卷包装长度: 12.48米.)
7. COMPONENT LOAD PER REEL: 1000 PCS. (每卷包装数量: 1000只.)
8. 纸箱装箱以不超过装箱线为准, 空余位置用塑料泡沫及保尼龙填充.
9. 纸箱分小、中、标准型3种规格型号: 装箱为整箱(左下包装量)采用标准型纸箱包装, 未达到整箱数量以产品量适当采用小型或中型纸箱包装.



纸箱型号 Carton Type	小型 Small Size	中型 Medium	标准型 Standard
高度 Hight (CM)	7.5	15	32

CKT (1.0mm pitch)	B0	W	F
2*4	7.00	16	7.50
2*5	8.00		
2*6	9.00		
2*7	10.00		
2*8	11.00		
2*9	12.00	24	11.50
2*10	13.00		
2*11	14.00		
2*12	15.00		
2*13	16.00		

CKT (1.0mm pitch)	W	PCS/RELL	RELL/CARTON	SUM (PCS)
2*4	16	1000	14	14000
2*5	16	1000	14	14000
2*6	24	1000	10	10000
2*7	24	1000	10	10000
2*8	24	1000	10	10000
2*9	24	1000	10	10000
2*10	24	1000	10	10000
2*11	24	1000	10	10000
2*12	24	1000	10	10000
2*13	24	1000	10	10000



THIS DOCUMENT IS THE
SOLE PROPERTY OF
BBJconn Technology Co.,Ltd.
Corporation AND SHOULD
NOT BE USED IN WHOLE
PRIOR WRITTEN PERMISSION.




PDWG NO: 0456-1

深圳市步步精科技有限公司



.X: ± 0.38 .XX: ± 0.25 .XXX: ± 0.13	X': $\pm 3'$.X': $\pm 2'$.XX': $\pm 1'$	NAME: 针座 SHLD1.0-2x6P B型 双排 立贴 带扣 4代 无柱 米黄色 加盖盖带
APPD	JM_Zheng	PJ NO: 123-244-120003-X3G
CHKD	Tang	SIZE: A4
DR	LYX	DRW NO:
		FINISH: SEE NOTES
		MAT'L: SEE NOTES
		SCALE: N/A
		REV: A0
		UNIT: mm
		PAGE: 2/3

NOTE(注):

1. 10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE $\pm 0.2\text{mm}$.
(10片孔距累积公差 $\pm 0.2\text{mm}$.)
2. CARRIER CAMBER NOT TO EXCEED 1mm IN 100mm.
(载带拱/弧形MAX:1/100mm.)
3. ALL DIMENSIONS MEET EIA-481 REQUIREMENTS.
(所有的尺寸要满足协会EIA-481规范.)
4. MATERIAL: CLEAR ANTISTATIC PS, COLD SEALING.
(载带材料: 透明抗静电 PS.)
5. THICKNESS: $0.35 \pm 0.05\text{mm}$. (载带厚度: $0.35 \pm 0.05\text{mm}$.)
6. PACKING LENGTH PER REEL: 12.48 METERS. (每卷包装长度: 12.48米.)
7. COMPONENT LOAD PER REEL: 1000 PCS. (每卷包装数量: 1000只.)
8. 纸箱装箱以不超过装箱线为准, 空余位置用塑料泡沫及保尼龙填充.
9. 纸箱装分小、中、标准型3种规格型号: 装箱为整箱(左下包装量)采用标准型纸箱包装, 未达到整箱数量以产品量适当采用小型或中型纸箱包装.



CKT (1.0mm pitch)	W	PCS/REEL	REEL/CARTON	SUM (PCS)
2*14	32	1000	8	8000
2*15		1000	8	8000
2*16		1000	8	8000
2*17		1000	8	8000
2*18		1000	8	8000
2*19	44	1000	6	6000
2*20		1000	6	6000
2*21		1000	6	6000
2*22		1000	6	6000
2*23		1000	6	6000
2*24	44	1000	6	6000
2*25		1000	6	6000
2*26		1000	6	6000
2*27		1000	6	6000
2*28		1000	6	6000
2*29		1000	6	6000
2*30		1000	6	6000



纸箱型号 Carton Type	小型 Small Size	中型 Medium	标准型 Standard
高度 Height (CM)	7.5	15	32

CKT (1.0mm pitch)	B0	W	F	S
2*14	17.00	32	14.2±0.15	28.40
2*15	18.00			
2*16	19.00			
2*17	20.00			
2*18	21.00			
2*19	22.00	44	20.2±0.15	40.40
2*20	23.00			
2*21	24.00			
2*22	25.00			
2*23	26.00			
2*24	27.00			
2*25	28.00			
2*26	29.00			
2*27	30.00			
2*28	31.00			
2*29	32.00			
2*30	33.00			

THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co., Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE PRIOR WRITTEN PERMISSION.

PDWG NO: 0456-1

深圳市步步精科技有限公司

NAME: 针座 SHLD1.0-2x6P B型 双排 立贴 带扣 4代 无柱 米黄色 加盖盖带

PJ NO: 123-244-120003-X3G

SIZE: A4

DRW NO:

FINISH: SEE NOTES

MAT'L: SEE NOTES

SCALE: N/A

REV: A0

UNIT: mm

PAGE: 3/3

APPD: JM_Zheng

CHKD: Tang

DR: LYX