



NOTE:

- 1.ELECTRICAL CHARACTERISTICS:
 - 1.1 CONTACT RESISTANCE:30mΩ MAX
 - 1.2 CONTACT CURRENT RATING:1.5A
 - 1.3 DIELECTRIC WITHSTANDING VOLTAGE:100 V R.M.S.
 - 1.4 INSULATION RESISTANCE 100 MΩ MIN
 - 1.5 OPERATING TEMPERATURE:-30°C ~ 80°C
- 2 MECHANICAL CHARACTERISTICS:
 - 2.1 MATING FORCE:3.57kgf MAX
 - 2.2 UNMATING FORCE:1.02kgf MIN
 - 2.3 DURABILITY:MANDATORY:1,500 CYCLES
- 3.PLATING
 - 3.1 TERMINAL:
 - 50u" MIN NICKEL ALL OVER
 - 100u"MIN Tin ON SOLDER AREA
 - (1~30)u"Au ON CONTACT AREA
 - 3.2 SHELL:80u"MIN.NICEL ALL OVER



THIS DOCUMENT IS THE
SOLE PROPERTY OF
BBJconn Technology Co.,Ltd.
Corporation AND SHOULD
NOT BE USED IN WHOLE
PRIOR WRITTEN PERMISSION.

PDWG NO: 0886-1



 深圳市步步精科技有限公司

.X: ±0.38 X: ±3"		NAME:USB 3.0 AF 90度 双层 L=17.50 四脚直插 端子DIP脚长2.6 卷边 LCP蓝胶 不锈钢外壳 盒装				
.XX: ±0.25 .X: ±2"						
.XXX: ±0.13 .XX: ±1"						
APPD	JM_Zheng		PJ NO: 127-272-090012-K4G			
CHKD	LYX		SIZE:A4	DRW NO:		
DR	SGF		FINISH:SEE NOTES		MAT'L:SEE NOTES	
		SCALE:N/A		REV:A0	UNIT:mm	PAGE:1/2



备注:
1. 包装要求整洁, 美观, 工整, 统一
2. 作业过程不可损坏产品, 轻拿轻放

包 装 信 息	
每盘产品数	100pcs
每一扎盘数	每扎10盘
每一箱盘数	20盘
每箱产品数	2000pcs
产品单重	/
每箱净重	以实际为准
每箱毛重	以实际为准
注: 尾数以实际为准, 填充纸带保护, 另做标识	

品 名	规格	单 位	用 量
吸塑盘上盖	USB AF双层专用吸塑盘上盖,PVC透明	PCS	1/100
吸塑盘下盒	USB AF双层专用吸塑盘下盖,PVC透明	PCS	1/100
纸板	K=K,21*26CM	PCS	4/2000
外箱	外箱K=K,	PCS	1/2000

THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE PRIOR WRITTEN PERMISSION. PDWG NO: 0886-1		深圳市步步精科技有限公司 工程 APPROVED		NAME:USB 3.0 AF 90度 双层 L=17.50 四脚直插 端 子DIP脚长2.6 卷边 LCP蓝胶 不锈钢外壳 盒装	
.X: ±0.38 .XX: ±0.25 .XXX: ±0.13		X': ±3' .X': ±2' .XX': ±1'		PJ NO: 127-272-090012-K4G	
APPD JM_Zheng		CHKD LYX		SIZE:A4 DRW NO:	
DR SGF		FINISH:SEE NOTES		MAT'L:SEE NOTES	
		SCALE:N/A		REV:A0	
		UNIT:mm		PAGE:2/2	