

REV	ECN NO	CONTENT	DATE	ENGINEER
A0		INITIAL RELEASE	/	LYX


Note:

1. Material:


- 1.1 Housing: thermoplastic high temp.UL94V-0;
- 1.2 Latch: thermoplastic high temp.UL94V-0;
- 1.3 Terminal: copper alloy.
- 1.4 Fitting Nail: copper alloy.

2. Finsh:

- 2.1 Terminal:
50~100u" Nickel under plating over all
Gold Flash on contact Solder
 - 2.2 Fitting Nail:
50~100u" Nickel under plating over all
80~150u" Matte-Tin over all.
3. Product must comply HF RoHS specification.



ALL TERMINAL AND SOLDER COPLANARITY IS 0.10mm Max.



CKTS	DIM A	DIM B	DIM C	DIM D	DIM E	DIM F
04	1.50	3.80	3.17	4.37	3.95	4.35
05	2.00	4.30	3.67	4.87	4.45	4.85
06	2.50	4.80	4.17	5.37	4.95	5.35
07	3.00	5.30	4.67	5.87	5.45	5.85
08	3.50	5.80	5.17	6.37	5.95	6.35
09	4.00	6.30	5.67	6.87	6.45	6.85
10	4.50	6.80	6.17	7.37	6.95	7.35
11	5.00	7.30	6.67	7.87	7.45	7.85
12	5.50	7.80	7.17	8.37	7.95	8.35
13	6.00	8.30	7.67	8.87	8.45	8.85
14	6.50	8.80	8.17	9.37	8.95	9.35
15	7.00	9.30	8.67	9.87	9.45	9.85
16	7.50	9.80	9.17	10.37	9.95	10.35
17	8.00	10.30	9.67	10.87	10.45	10.85
18	8.50	10.80	10.17	11.37	10.95	11.35
19	9.00	11.30	10.67	11.87	11.45	11.85
20	9.50	11.80	11.17	12.37	11.95	12.35
21	10.00	12.30	11.67	12.87	12.45	12.85
22	10.50	12.80	12.17	13.37	12.95	13.35
23	11.00	13.30	12.67	13.87	13.45	13.85
24	11.50	13.80	13.17	14.37	13.95	14.35
25	12.00	14.30	13.67	14.87	14.45	14.85
26	12.50	14.80	14.17	15.37	14.95	15.35
27	13.00	15.30	14.67	15.87	15.45	15.85
28	13.50	15.80	15.17	16.37	15.95	16.35
29	14.00	16.30	15.67	16.87	16.45	16.85
30	14.50	16.80	16.17	17.37	16.95	17.35
31	15.00	17.30	16.67	17.87	17.45	17.85
32	15.50	17.80	17.17	18.37	17.95	18.35
33	16.00	18.30	17.67	18.87	18.45	18.85
34	16.50	18.80	18.17	19.37	18.95	19.35
35	17.00	19.30	18.67	19.87	19.45	19.85
36	17.50	19.80	19.17	20.37	19.95	20.35
37	18.00	20.30	19.67	20.87	20.45	20.85
38	18.50	20.80	20.17	21.37	20.95	21.35
39	19.00	21.30	20.67	21.87	21.45	21.85
40	19.50	21.80	21.17	22.37	21.95	22.35



RECOMMENDED P.C.B PATTERN LAYOUT

RECOMMENDED FPC/FFC DIMENSION



THIS DOCUMENT IS THE
SOLE PROPERTY OF
BBJconn Technology Co.,Ltd.
Corporation AND SHOULD
NOT BE USED IN WHOLE
PRIOR WRITTEN PERMISSION.



深圳市步步精科技有限公司

NAME:

FPC 0.5-34P 翻盖下接 H=0.95 编带

APPD

JM_Zheng

CHKD

Tang

PDWG NO:0407-1

DR

LYX

PJ NO:

130-221-340004-W3G

SIZE:

A4

REV:

A0

UNIT:

mm

DRW NO:

FINISH:

SEE NOTES

MAT'L:

SEE NOTES

PAGE:





1/2

REV	ECN NO	CONTENT	DATE	ENGINEER
A0		INITIAL RELEASE	/	LYX

NOTES:

1. 10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE. $\pm 0.20\text{mm}$
2. CARRIER CAMBER NOT TO EXCEED 1mm IN 250mm.
3. ALL DIMENSIONS MEET EIA-481-C REQUIREMENTS.
4. MATERIAL: BLACK ANTI-STATIC POLYSTYRENE.
5. THICKNESS: $0.30 \pm 0.05 \text{ mm}$.
6. PACKING LENGTH PER 13" REEL : 36.60METERS.
7. COMPONENT LOAD PER 13" REEL : 3000PCS.
8. PEELING OFF FORCE OF TOP TAPE 0.1N~0.7N(10.2gf~71.4gf).

黑色(3000PCS/Reel)
白色(3000PCS/Reel)
白色(4000PCS/Reel)



CNYS	B0±0.10	W	W1	F	S0±0.10
4	4.67				
5	5.17				
6	5.67				
7	6.17				
8	6.67	16±0.30	16.4	7.5±0.10	
9	7.17				
10	7.67				
11	8.17				
12	8.67				
13	9.17				
14	9.67				
15	10.17				
16	10.67				
17	11.17				
18	11.67				
19	12.17				
20	12.67				
21	13.17	24±0.30	24.4	11.5±0.10	
22	13.67				
23	14.17				
24	14.67				
25	15.17				
26	15.67				
27	16.17				
28	16.67				
29	17.17				
30	17.67				
31	18.17				
32	18.67				
33	19.17				
34	19.67	32±0.30	32.4	14.2±0.10	28.4
35	20.17				
36	20.67				
37	21.17				
38	21.67				
39	22.17				
40	22.67	44±0.30	44.4	20.2±0.15	40.4

THIS DOCUMENT IS THE
SOLE PROPERTY OF
BBJconn Technology Co.,Ltd.
Corporation AND SHOULD
NOT BE USED IN WHOLE
PRIOR WRITTEN PERMISSION.

深圳市步步精科技有限公司

NAME:	FPC 0.5-34P 翻盖下接 H=0.95 编带		
PJ NO:	130-221-340004-W3G		
SIZE:A4	DRW NO:		
FINISH:SEE NOTES	MAT'L:SEE NOTES		
SCALE:N/A	REV:A0	UNIT:mm	PAGE:2/2

PDWG NO:0407-1

DR

LYX