





REV.	ECN NO	CONTENT	DATE	ENGINEER
A0				

规格:

1. 额定值: DC30V 7A
2. 接触电阻: $\leq 30m\Omega$
3. 绝缘电阻: $\geq 100M\Omega$
4. 耐电压: 500VAC
5. 插拔力: 3N~30N
6. 使用寿命: 5000次
7. 使用温度: $-20^{\circ}C \sim +80^{\circ}C$



推荐插头尺寸




7	面板	不锈钢 T=0.1mm	1	本色
6	上盖	磷铜 T=0.2mm	1	CuSn打底1 μm , Sn表面0.15 μm
5	主体	PA9T	1	黑色
4	平片	黄铜 T=0.3mm	1	CuSn打底1 μm , Sn表面0.15 μm
3	弯片	黄铜 T=0.4mm	1	
2	弹片	磷铜 T=0.3mm	1	
1	PIN针	黄铜	1	
序号	名称	材料	数量	颜色/电镀

P.C.B 设计参考尺寸


THIS DOCUMENT IS THE
SOLE PROPERTY OF
BBJconn Technology Co.,Ltd.
Corporation AND SHOULD
NOT BE USED IN WHOLE
OR IN PART WITHOUT
PRIOR WRITTEN PERMISSION.
PDWG.NO: 0050-2

深圳市步步精科技有限公司	
.X: ± 0.38 .XX: ± 0.25 .XXX: ± 0.13	X*: $\pm 3^*$.X*: $\pm 2^*$.XX*: $\pm 1^*$
NAME: DC插座 DC-044A 2.0针 全铜 全包 五脚插 短柱 大电流7A	
APPD. JM_Zheng	PJ. NO.: 116-302-050003-Y2G
CHKD. LYX	SIZE: A4 DRW NO.:
DR. TSP	FINISH: SEE NOTES MAT'L.: SEE NOTES
SCALE: N/A REV.: A0 UNIT: mm PAGE: 1/2	

PE袋规格: 260*185



成品标签



1. 包装要求:

- 1.1 每个PE袋包装500pcs;
- 1.2 每1袋放一小纸盒;
- 1.3 每20个小纸盒放一个纸箱, 共计10000pcs;
- 1.4 纸箱外贴上标签



THIS DOCUMENT IS THE SOLE PROPERTY OF BBJconn Technology Co.,Ltd. Corporation AND SHOULD NOT BE USED IN WHOLE OR IN PART WITHOUT PRIOR WRITTEN PERMISSION.		深圳市步步精科技有限公司	
PDWG.NO: 0050-2		NAME: DC插座 DC-044A 2.0针 全铜 全包 五脚插 短柱 大电流7A	
APPD.	JM_Zheng	PJ. NO.:116-302-050003-Y2G	
CHKD.	LYX	SIZE: A4	DRW NO.:
		FINISH: SEE NOTES	MAT'L.: SEE NOTES
		SCALE: N/A	REV.: A0 UNIT: mm PAGE: 2/2